

SUBSTITUTE SPECIFICATION

1

A CABIN STRUCTURE FOR A WORKING MACHINE

BACKGROUND OF THE INVENTION

5 1. Field of the invention

The invention relates to a cabin structure for a working machine.

2. Description of the Related Art

10 According to prior art (e.g. SE patent publication 509528), the control
mechanism is normally placed between the cabin structure and the
frame of the working machine. Although these solutions have been
functional as such, they have, at least in some applications, resulted in
15 impractical constructions, because the requirement for space taken by
the control mechanism increases the main dimensions of the working
machine, *i.e.* its width, length and height. Other control mechanisms are
presented in DE application publication 3405921, whose inclination is
uncomfortable for the operator because of swinging. In the above-
20 mentioned control mechanism, as well as in EP application publication
636512, the moving means are placed in such a way that levelling of
the mechanism will cause tilting of the seat, which, in turn, must be
corrected again by levelling.

25 SUMMARY OF THE INVENTION

It is an aim of this invention to present a novel cabin structure, whereby it is possible to provide, to a great extent, the movements of the cabin structure according to prior art, while also providing new possibilities for moving the cabin structure. Furthermore, the cabin structure according to the invention makes it possible that the main dimensions of the working machine are not increased, if so desired, but they can be kept reasonable, even though the control mechanism is more versatile. From the point of view of the operator of the working machine, the cabin structure meets the demands set for modern working facilities.

SUB
SPEC
#6/A
N.E.
AGW
JUNE
10
2002

With the solution presented above, as the cabin element is stationary in relation to the frame of the working machine, a compact unit is provided, in which the control mechanism can be placed in a small space and it can also include third means for rotating the working base around the Z axis.

According to a particularly advantageous embodiment, the first and second means of the control mechanism for tilting of the working base are placed underneath the third means of the control mechanism. This solution has the advantage that the rotating of the working base around the Z axis can be implemented in a continuous manner after the leveling step performed by the first and second means in each working position of the working machine.

Furthermore, it is advantageous that the movements of the first and second means of the control mechanism for tilting of the working base are fitted to take place around a substantially joint centre of motion, preferably in such a way that the substantially joint centre of motion is on the Z axis. In this way, the ease at work of the person using the working means on the working base is ^{optimised} ~~optimised~~, particularly when the centre of motion of the control mechanism is placed above the seat part of the seat intended for the operator of the working machine, to be preferably placed substantially at the level of the operator's hip.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described in the description hereinbelow, in which reference is made to the embodiment shown in the appended drawings. In the drawings,

Fig. 1 shows schematically, in a slanted perspective view from above, a working machine, in connection with which an application of the cabin structure according to the invention is placed,

Fig. 2 shows, also in a slanted perspective view from above, an application of the cabin structure according to Fig. 1,

Fig. 3 shows, further in a slanted perspective view from above, tools and a control mechanism, which are used in connection with the application of the cabin structure according to Fig. 2,

Fig. 4 shows the cabin structure according to Fig. 2 in a vertical cross-section, and

Fig. 5 shows, in a slanted perspective view from above, the seat and control mechanism for the cabin structure according to Fig. 2.

DETAILED DESCRIPTION OF THE INVENTION

Particularly with reference to Fig. 1, the cabin structure 1 is placed in connection with the working machine 2. In the presented application, the working machine is a forest working machine with frame steering, Fig. 1 showing only its most important parts. The cabin structure 1 (*cf.* particularly Figs. 2 to 4) comprises a substantially transparent cabin element 4 equipped with a bottom part 3, as well as working means 5, 6 placed inside the cabin element 4, *i.e.* a seat 5 for the operator K of the working machine 2, and display and control means 6 for controlling the operations of the working machine 2. The cabin structure 1 also comprises a control mechanism 7 with means 7a, 7b and 7c coupled to each other, *i.e.* the first 7a and second 7b means for tilting the working means 5, 6 in relation to the body of the working machine 2 as well as in the planes XZ and YZ, and the third 7c means for rotating the working base around the Z axis. The orthogonal XYZ coordinate system is shown in Fig. 2, wherein the X direction is the horizontal longitudinal direction of the working machine, the Y direction is the horizontal transverse direction of the working machine (that is, the X and Y directions are perpendicular to each other), and the Z direction is the vertical direction.

According to a basic idea of the invention, the cabin element 4 is arranged to be substantially stationary in relation to the frame of the working machine 2. The outer surface of the bottom part 3 of the cabin element 4 is provided with connecting means 8, particularly lugs shown in Fig. 2, to connect the cabin structure 1 to the frame of the working machine 2. The bottom part 3 of the cabin element 4 is arranged to have a downwards reducing horizontal cross-section.

Furthermore, the working means 5, 6 are placed on a working base 9 placed on the bottom part 3 of the cabin element 4. In the presented embodiment, the shape of the working base 9 is a substantially circular plane surface, which also substantially constitutes the functional floor surface of the cabin structure 1. To the outer edge of the working base 9 is fixed an annular collar part 10a whose outer surface has an at least spherical shape and which extends downwards from the outer edge, towards the centre of the working base 9. Particularly for reasons of space saving, the working base 9 is elevated from its basic level underneath the seat part 5a of the seat 5 (see truncated conical part 9a in Fig. 4), wherein the space formed inside the elevated part 9a, underneath the seat part 5a of the seat 5, accommodates parts of the control mechanism 7, at least the third means 7c for rotating the working base around the Z axis.

As shown particularly in Fig. 4, the control mechanism 7 is placed between the working base 9 (in reality, in horizontal position VA) and the bottom part 3 of the cabin element 4 (in reality, tilted according to the frame position KA) so that the first 7a and second 7b means of the control mechanism 7 for tilting the working base are placed, in the height direction, underneath the third 7c means of the control mechanism 7. Furthermore, the movements of the first 7a and second 7b means of the control mechanism 7 for tilting the working base 9 are arranged to be effected around a substantially joint movement centre LKP, wherein this movement centre LKP is preferably on the Z axis and placed above the seat part 5a of the seat 5 intended for the operator K of the working machine 2, preferably to be placed substan-

tially at the level of the operator's K hip, as shown in Fig. 5. The detailed structure of the control mechanism 7 itself will not be described in this context, because *e.g.* the applicant's previous FI patent application 991449 discloses a position adjustment mechanism which can, when modified, also be applied in the applications of the present invention.

The working base 9 and the bottom part 3 of the cabin element 4 of the cabin structure 1 are thus connected by the control mechanism 7 so that the lower one 7a of the first and second means 7a, 7b implementing the tilting of the working base 9 in relation to the frame of the working machine 2 is connected to the bottom part 3, for example, by means of a flange support, and the third 7c means for rotating the working base 9 are connected to the working base 9, its lower surface, for example to the central elevated part 9a in connection with the working base 9.

A cover arrangement 10a, 10b is placed in the point of linkage between the bottom part 3 and the working base 9 to connect the working base 9, separate from the control mechanism 7, to the cabin element 4 during their respective movements. The cover arrangement 10a, 10b preferably consists of two parts in such a way that its first part 10a, *i.e.* the annular collar part which is connected to the outer edge of the working base 9, at least its outer surface having a spherical shape, extends downwards, and the second part 10b consists of that part of the inner surface 3a of the bottom part 3 which is exposed during the movements of the working base 9, as shown in Fig. 4. To provide the system of movements presented above, it is advantageous that the shape of the bottom part 3 of the cabin element 4, at least of the inner surface 3a, at least on that range of height dimension in which the working base 9 moves during the respective movements of the working base 9 and the frame of the working machine 2, is a spherical surface, preferably so that the whole bottom part 3 of the cabin element 4, at least on the side of the inner surface, is substantially spherical. In the embodiment presented in the drawings, the bottom part 3 is, substantially as a whole, a sheet-like form piece with a spherical shape, whose

upper edge 3b is connected to a substantially horizontal collar part 11 formed at the lower edge 4a of the cabin element 4. Thus, in the presented embodiment, the horizontal cross-section of the bottom part 3 of the cabin element 4 reduces downwards, which makes it possible to save space, particularly in the height direction of the working machine. Furthermore, the centre KK of the spherical form of the inner surface 3a of the bottom part 3 (Fig. 4) is placed above the seat part 5a of the seat 5, by the hip of the operator K. Preferably, the centre KK joins the movement centre LKP (see also Fig. 5). The diameter of the circular working base 9 is selected so that it is substantially placed in the upper part of the spherical shape of the bottom part 3, touching the spherical shape at the whole length of its circumference, wherein the annular collar part 10, whose outer surface has an at least spherical shape and which forms the first part of the cover arrangement 10a, 10b, is placed on the inner surface 8a of the bottom part 3.

The present invention is not limited solely to the above-presented and exemplified preferred embodiments, but it can be modified within the scope of the appended claims.

1. A cabin structure for a working machine, comprising:

- 1000

- 35 2. A cabin structure according to claim 1, wherein the working base is circular and is arranged touchingly at the inner surface of the bottom part, whose shape is a spherical surface at least on that range of height dimension in which the outer edge of the working base moves during respective movements of the working base and the frame of the

working machine, wherein the centre of the spherical shape is placed in said movement centre.

- 5 3. A cabin structure according to claim 2, wherein the diameter of the working base is selected so that the working base is placed substantially at the upper edge of the spherical shape formed by the inner surface, touching the spherical shape at the whole length of its circumference.
- 10 4. A cabin structure according to claim 2, wherein the outer edge of the working base is provided with a downwards extending annular collar part which has at least an outer surface which is spherical and which is placed on the bottom part.
- 15 5. A cabin structure according to claim 1, wherein the movement centre is placed above the seat part of the seat, preferably substantially at the level of the hip of the operator.
- 20 6. A cabin structure according to claim 1, wherein the lower one of the first and second means is connected to the bottom part, and the third means are connected to the working base.
- 25 7. A cabin structure according to claim 1, wherein the working base comprises an elevated part underneath the seat part of the seat, wherein at least the third means are placed in the space formed in connection with the elevated part.
- 30 8. A cabin structure according to claim 1, wherein a cover arrangement, separate from the control mechanism, is placed at the point of linkage between the bottom part and the working base to connect the working base to the cabin element during their respective movements, and that the first part of the cover arrangement is placed at the edge of the working base, to extend downwards, and the second part consists of the inner edge of the bottom part.

9. A cabin structure according to claim 8, wherein the first part of the cover arrangement consists of the collar part of the working base, which has at least an outer surface with a spherical shape and which is placed on the bottom part.

5

10. A cabin structure according to claim 1, wherein the bottom part is a sheet-like ^{thin} form piece which is connected at its upper edge to a substantially horizontal collar part formed at the lower edge of the cabin element.

10

11. A cabin structure according to claim 1, wherein the bottom part is designed to have a downwards reducing horizontal cross-section, (for example) in such a way that the whole bottom part is, at least on the side of the inner surface, substantially spherical.

15

12. A cabin structure according to claim 1, wherein the outer surface of the bottom part of the cabin element comprises connecting means for connecting the cabin structure to the frame of the working machine.

20

13. A cabin structure for a working machine, comprising:

— a cabin element which is equipped with a bottom part and which is substantially stationary in relation to the working machine,

25

— working means placed inside the cabin element, comprising a seat for the operator of the working machine as well as display and control means for controlling the operations of the working machine,

for —

— a movable working base, on which the working means are placed, and

30

— a control mechanism for levelling the working position of the operator, comprising first and second means for tilting the working base in the longitudinal direction and the transverse direction of the working machine, and third means for rotating the working base around a vertical axis of rotation,

35

wherein

- 5 — the movements of the first and second means are arranged to take place around a joint movement centre in such a way that the movement centre is placed on said vertical axis of rotation and also above the working base,
 - the working base is placed above the bottom part, and the control mechanism, in turn, is placed between the working base and the bottom part, and
 - 10 — the working base is circular and is arranged touchingly at the inner surface of the bottom part, whose shape is a spherical surface at least on that range of height dimension in which the outer edge of the working base moves during levelling movements of the working base, wherein the
 - 15 centre of the spherical shape is placed in said movement centre.
14. A cabin structure according to claim 13, wherein the diameter of the working base is selected so that the working base is placed
- 20 substantially at the upper edge of the spherical shape formed by the inner surface, touching the spherical shape at the whole length of its circumference.
15. A cabin structure according to claim 13, wherein the outer edge of
- 25 the working base is provided with a downwards extending annular collar part which has at least an outer surface which is spherical and which is placed on top of the bottom part.
16. A cabin structure according to claim 14, wherein the outer edge of
- 30 the working base is provided with a downwards extending annular collar part which has at least an outer surface which is spherical and which is placed on top of the bottom part.
17. A cabin structure according to claim 5, wherein the lower one of
- 35 the first and second means is connected to the bottom part, and the third means are connected to the working base.

5

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2818

5
10
15
20

20